



Printing date 09.11.2022 Version number 10.3 Revision: 09.11.2022

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Power Lock
- · Nanoforms The mixture does not contain any components in nanoform
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Sealing
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Menzerna polishing compounds GmbH & Co. KG Industriestraße 25 76470 ÖTIGHEIM GERMANY

sds@menzerna.com Tel.: +49 (0) 7222 9157-0 www.menzerna.com

- · Further information obtainable from: Product and Environmental Safety Department
- 1.4 Emergency telephone number: CHEMTREC: +1 703-741-5970 / 1-800-424-9300 CCN 842438

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

STOT RE 2 H373 May cause damage to the central nervous system through prolonged or repeated exposure.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



- Signal word Warning
- Hazard-determining components of labelling:

Stoddard solvent

· Hazard statements

H373 May cause damage to the central nervous system through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P314 Get medical advice/attention if you feel unwell.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)





Printing date 09.11.2022 Version number 10.3 Revision: 09.11.2022

Trade name: Power Lock

(Contd. of page 1)

#### · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking. EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:			
EC number: 927-676-8	Hydrocarbons, C12-C16, isoalkanes, cyclics,<2% aromatics	10-25%	
Reg.nr.: 01-2119456377-30	♦ Asp. Tox. 1, H304, EUH066		
EC number: 920-901-0	Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	2.5-10%	
Reg.nr.: 01-2119456810-40	♦ Asp. Tox. 1, H304, EUH066		
CAS: 71750-80-6	Siloxanes and silicones, di-Me,[[[3-[(2-aminoethyl)amino]	≥2.5-<10%	
EC number: 615-337-4	propyl]dimethoxysilyl]oxy]-terminated		
	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319		
CAS: 8052-41-3	Stoddard solvent	≥2.5-<10%	
EINECS: 232-489-3	♦ Flam. Liq. 3, H226; ♦ Acute Tox. 3, H331; ♦ STOT RE 1, H372; Asp. Tox. 1, H304; ♦ Skin Irrit. 2, H315; Aquatic Chronic 3, H412		
CAS: 67-63-0	propan-2-ol	≥0-<10%	
EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336		
CAS: 69430-37-1 Polymer	Dimethyl Siloxane, HO-term Rxn Methyltrimethoxysilane & Aminoethylaminopropyltrimethoxysilane	≥0.25-<2.5%	
	♦ Flam. Liq. 2, H225; ♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319		
CAS: 67-56-1	methanol	≥0-≤2.5%	
EINECS: 200-659-6	♦ Flam. Liq. 2, H225; ♦ Acute Tox. 3, H301; Acute Tox. 3,		
	H311; Acute Tox. 3, H331; ♦ STOT SE 1, H370 Specific concentration limits: STOT SE 1; H370: C ≥ 10 %		
	STOT SE 2; H371: 3 % ≤ C <		
	10 %		
CAS: 2634-33-5	1,2-benzisothiazol-3(2H)-one	≥0-<0.05%	
EINECS: 220-120-9 Reg.nr.: 01-2120761540-60	Acute Tox. 2, H330; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317		
	Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 %		
CAS: 52-51-7	bronopol (INN)	≥0.025-<0.25%	
EINECS: 200-143-0	<ul> <li>♦ Eye Dam. 1, H318;</li> <li>♦ Aquatic Acute 1, H400 (M=10);</li> <li>Aquatic Chronic 1, H410 (M=1);</li> <li>♦ Acute Tox. 4, H312;</li> <li>Skin Irrit. 2, H315;</li> <li>STOT SE 3, H335</li> </ul>		

Additional information: For the wording of the listed hazard phrases refer to section 16.





Printing date 09.11.2022 Version number 10.3 Revision: 09.11.2022

Trade name: Power Lock

(Contd. of page 2)

## SECTION 4: First aid measures

## · 4.1 Description of first aid measures

#### · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation: Supply fresh air; consult doctor in case of complaints.

### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

#### · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

### After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

### · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

Treat according to symptoms.

## \* SECTION 5: Firefighting measures

## · 5.1 Extinguishing media

- · Suitable extinguishing agents: Water spray, foam, dry powder or carbon dioxide.
- · For safety reasons unsuitable extinguishing agents: Water with full jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Nitrogen oxides (NOx)

## 5.3 Advice for firefighters

**Protective equipment:** 

Wear self-contained respiratory protective device.

Wear fully protective suit.

## SECTION 6: Accidental release measures

### · 6.1 Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Ensure adequate ventilation. Use personal protection recommended in section 8.

## · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

### · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

EU -





Printing date 09.11.2022 Version number 10.3 Revision: 09.11.2022

Trade name: Power Lock

(Contd. of page 3)

## \* SECTION 7: Handling and storage

### · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:

soil

PNEC (secondary poisoning)

CAS: 67-56-1 methanol PNEC (Sewage plant)

PNEC (freshwater)

Requirements to be met by storerooms and receptacles:

Store in a well-ventilated place. Storage temperature: between 5°C and 30°C.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

28 mg/kg

100 mg/l

20,800 µg/l

160 mg/kg Nahrung

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

CAS: 67-56-1 methanol (≤2.5%)				
IOELV Long-term value: 260 mg/m³, 200 ppm Skin				
L	SK			
	· DNELs			
	CAS: 67-6	3-0 propan-2-ol		
ľ	Oral	DNEL, general pop	oulation, oral	26 mg/kg bw/d (general population)
	Dermal	DNEL, general pop	oulation, dermal	319 mg/kg KG/d (general population)
		DNEL, worker, der	mal	888 mg/kg KG/d (worker)
	Inhalative	DNEL, general pop	oulation, inhalativ	89 mg/m3 (general population)
		DNEL, worker, inha	alativ	500 mg/m3 (worker)
Ī	CAS: 2634	4-33-5 1,2-benzisot	thiazol-3(2H)-on	e
ľ	Dermal	DNEL, general pop	oulation, dermal	0.345 mg/kg KG/d (general population)
		DNEL, worker, der	mal	0.966 mg/kg KG/d (worker)
	Inhalative	DNEL, general pop	oulation, inhalativ	1.2 mg/m3 (general population)
		DNEL, worker, inha	alativ	6.81 mg/m3 (worker)
PNECs				
CAS: 67-63-0 propan-2-ol				
PNEC (Sewage plant) 2,251 mg/l		2,251 mg/l		
PNEC (freshwater) 140,900 µg/l		140,900 µg/l		
PNEC (seawater) 140.9 mg/l		140.9 mg/l		
	PNEC (see	diment)	552 mg/kg	
П	`	•		

(Contd. on page 5)





Printing date 09.11.2022 Version number 10.3 Revision: 09.11.2022

Trade name: Power Lock

		(Contd. of page 4)
PNEC (seawater)	2.08 mg/l	
sediment (freshwater)	77 mg/kg	
Sediment (seawater)	7.7 mg/kg	
soil	100 mg/kg	
CAS: 2634-33-5 1,2-benz	sothiazol-3(2H)-one	
PNEC (Sewage plant)	1.03 mg/l	
PNEC (freshwater)	4.03 μg/l	
PNEC (seawater)	0.000403 mg/l	
sediment (freshwater)	0.0499 mg/kg	
Sediment (seawater)	0.00499 mg/kg	
soil	3 mg/kg	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

Normally one does not come into direct contact with the product during use. At the risk of entanglement of protective glove in rotating or linear moving machine parts protective gloves should not be worn. Recommendation for short-term exposure: Use chemical resistant gloves.

#### Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.45 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.


### · Penetration time of glove material

≥ 480 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

## · Eye/face protection

Safety glasses







Version number 10.3 Revision: 09.11.2022 Printing date 09.11.2022

Trade name: Power Lock

(Contd. of page 5)

· Body protection: Protective work clothing

## SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid · Colour: Green · Odour: Solvent-like · Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

range

>100 °C (>212 °F) · Flammability Not applicable.

· Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined.

48 °C (118.4 °F) (DIN EN ISO 3679 Verf. B) · Flash point:

Not determined. · Decomposition temperature:

· pH at 20 °C (68 °F) 7-10

· Viscosity:

Kinematic viscosity at 40 °C (104 °F) >20.5 mm<sup>2</sup>/s · Dynamic: Not determined.

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure: Not determined.

· Density and/or relative density

Density at 20 °C (68 °F): 1 g/cm3 (8.35 lbs/gal)

Relative density Not determined. Not determined. · Vapour density

· 9.2 Other information CLP Annex 1, 2.6.4.5 Liquids with a flash point of

more than 35 °C and not more than 60 °C need not be classified in Category 3 if negative results have been obtained in the sustained combustibility test L.2, Part III, section 32 of the UN RTDG, Manual of Tests

and Criteria. Result: negative

· Appearance:

· Form: Viscous

· Important information on protection of health and environment, and on safety.

**Auto-ignition temperature:** Product is not selfigniting.

· Explosive properties: Product does not present an explosion hazard.

· Solvent content:

· VOC (EC) 10.29-10.93 %

· Change in condition Softening point/range

· Oxidising properties Not determined.

(Contd. on page 7)





Printing date 09.11.2022 Version number 10.3 Revision: 09.11.2022

Trade name: Power Lock

(Contd. of page 6)

· Evaporation rate	Not determined.	
· Information with regard to physical hazard		
classes		
· Explosives	Void	
· Flammable gases	Void	
Aerosols	Void	
· Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamn	nable	
gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
Corrosive to metals	Void	
<ul> <li>Desensitised explosives</li> </ul>	Void	

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity None under normal conditions.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50	· LD/LC50 values relevant for classification:			
Hydrocar	Hydrocarbons, C11-C13, isoalkanes, <2% aromatics			
Oral	LD50	>5,000 mg/kg (rat)		
Dermal	LD50	>3,000 mg/kg (rab)		
CAS: 805	CAS: 8052-41-3 Stoddard solvent			
Oral	LD50	>5,000 mg/kg (rat)		
Dermal	LD50	>3,000 mg/kg (rab)		
CAS: 67-6	CAS: 67-63-0 propan-2-ol			
Oral	LD50	5,840 mg/kg (rat)		
Dermal	LD50	13,900 mg/kg (rabbit)		

(Contd. on page 8)





Printing date 09.11.2022 Version number 10.3 Revision: 09.11.2022

Trade name: Power Lock

		(Contd. of page 7)	
Inhalative	LC50/4 h	>25 mg/l (rat)	
CAS: 67-5	6-1 metha	anol	
Oral	LD50	340 mg/kg (humans) (Schätzwert)	
		5,628 mg/kg (rat)	
	LD50	29-237 ml (humans) (Schätzwert)	
Dermal	LD50	15,800 mg/kg (rabbit)	
CAS: 2634	CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one		
Oral	LD50	670-784 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rat)	
Inhalative	LC50/4 h	0.5 mg/l (rat)	
CAS: 52-5	1-7 brono	pol (INN)	
Oral	LD50	305 mg/kg (rat)	

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure

May cause damage to the central nervous system through prolonged or repeated exposure.

- · Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards

· Endocrine disrupting properties			
CAS: 540-97-6	Dodecamethylcyclohexasiloxane	List II	
CAS: 541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	List II	
CAS: 556-67-2	octamethylcyclotetrasiloxane	List II, III	

## SECTION 12: Ecological information

## · 12.1 Toxicity

· Aquatic toxicity:		
CAS: 8052-41-3	Stoddard solvent	
LC50/96h	3.5 mg/l (Chaetogammarus marinus)	
	2.5 mg/l (Oncorhynchus mykiss)	
NOEC (96h)	0.16 mg/l (Pseudokirchneriella subcapitata)	
NOEC (21d)	0.28 mg/l (daphnia)	
NOEC (112d)	<1.4 mg/l (Oncorhynchus mykiss)	
ErC50 (96h)	1.2 mg/l (Pseudokirchneriella subcapitata)	
CAS: 67-63-0 pro	opan-2-ol	
LC50/24h	9,714 mg/l (daphnia)	
LC50/96h	9,640 mg/l (pimephales promelas)	
EC50	>100 mg/l (bacteria)	
EC50 (72h)	>100 mg/l (Scenedesmus subspicatus)	
	(Contd. on page 9)	





Printing date 09.11.2022 Version number 10.3 Revision: 09.11.2022

Trade name: Power Lock

	(Contd. of page
	imethyl Siloxane, HO-term Rxn Methyltrimethoxysilane & minoethylaminopropyltrimethoxysilane
EC50 (48h)	>0.1-1 mg/l
CAS: 67-56-1 meth	anol
aquatic toxicity	>10,000 mg/l (daphnia)
LC50/96h	15,400 mg/l (Lepomis macrochirus)
ErC50 (96h)	22,000 mg/l (Pseudokirchneriella subcapitata)
CAS: 2634-33-5 1,2	-benzisothiazol-3(2H)-one
LC50/96h	2.2 mg/l (Oncorhynchus mykiss)
EC50 (48h) (static)	0.643 mg/l (daphnia)
EC50 (72h)	0.11 mg/l (Selenastrum capricornutum)
EC50 (96h) (static)	0.9893 mg/l (Mysidopsis bahia)
NOEC (72h)	0.04 mg/l (Selenastrum capricornutum)
NOEC (96h) (static)	0.25 mg/l (Mysidopsis bahia)
NOEC (21d)	1.2 mg/l (daphnia)
NOEC (28d)	0.21 mg/l (Oncorhynchus mykiss)
ErC50 (72h)	0.15 mg/l (Pseudokirchneriella subcapitata)
CAS: 52-51-7 brone	ppol (INN)
LC50/96h	3 mg/l (Oncorhynchus mykiss)
EC50 (3h)	13 mg/l (sewage plant)
EC50 (48h)	1.04 mg/l (dah)
EC50 (72h)	0.068 mg/l (al)
NOEC (72h)	0.0025 mg/l (al)
NOEC (21d)	0.06 mg/l (dah)
NOEC (28d)	2.61 mg/l (Oncorhynchus mykiss)
12.2 Persistence a	nd degradability
CAS: 8052-41-3 Std	oddard solvent
degradability >63 %	
CAS: 67-63-0 propa	
degradability 53 %	(consumption of oxygene (time 5d))
12.3 Bioaccumulat	ive potential
CAS: 8052-41-3 Std	ddard solvent
log KOW 5.25 /gem	essen
CAS: 67-63-0 propa	an-2-ol
log KOW 0.05	
CAS: 67-56-1 meth	anol
BCF <100	
<10 /gem	essen (Leuciscus idus)

- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11. (Contd. on page 10)





Printing date 09.11.2022 Version number 10.3 Revision: 09.11.2022

Trade name: Power Lock

(Contd. of page 9)

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

Harmful to aquatic organisms

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste disposal key:

Waste codes should be determined in consultation with the customer, supplier and disposal.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

## **SECTION 14: Transport information**

· 14.1 UN number or ID number · ADR/RID, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR/RID, ADN, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR/RID, ADN, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR/RID, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk according instruments	to IMO Not applicable.
· UN "Model Regulation":	Void

## **SECTION 15: Regulatory information**

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Regulation 1907/2006/EC, REACH concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (in the currently valid version)

Regulation 1272/2008/EC, on Classification, Labelling and Packaging of substances and mixtures (in the currently valid version)

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 11)





Printing date 09.11.2022 Version number 10.3 Revision: 09.11.2022

Trade name: Power Lock

(Contd. of page 10)

- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 69
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

The information in the safety data sheet applies only to the product described in connection with its intended use. The information is based on the current state of our knowledge. In particular, they serve to describe our product with regard to the hazards it presents and the applicable safety precautions. They do not represent any assurance of product and quality properties. The information in this safety data sheet is required in accordance with Article 31 and Annex II of Regulation (EC) No 1907/2006.

#### · Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H370 Causes damage to organs.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 12)





Printing date 09.11.2022 Version number 10.3 Revision: 09.11.2022

Trade name: Power Lock

(Contd. of page 11)

### Classification according to Regulation (EC) No 1272/2008

Specific target organ toxicity (repeated exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Department issuing SDS: Product and Environmental Safety Department

Date of previous version: 03.03.2022

### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 2: Acute toxicity – Category 2
Acute Tox. 2: Acute toxicity – Category 2
Acute Tox. 3: Acute toxicity – Category 3

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* Data compared to the previous version altered.